



PRODUCT DATA SHEET

BIOSTRIP **Eco Friendly Release Agent**

Description

Biostrip is a Biodiesel based releasing agent, for the construction industry

Principal uses

Biostrip is suitable for use on timber, steel and fibreglass shuttering

Advantages

- Biostrip is eco friendly and biodegradable
- A simple one coat application is required
- Cleaning is minimised
- Biostrip does not evaporate in the sun
- Build up on the shutter is eliminated

Performance data

Appearance: Light/Medium Coloured Oil
Temperature Stability: 40°C
Flash Point: 198°C
Odour: Slight
Viscosity: 46
Physical Form: Liquid
Shelf Life: 6 Months

Application

Apply as thinly as possible to entire surface of shutter by means of a paint brush, paint roller or low pressure spray

Coverage

Coverage is approximately 14-20m² per litre

Packaging

Biostrip is available in 210ℓ and 25ℓ drums

Safety & handling

Use gloves and eye protection at all times. Should the product come into contact with eyes, wash immediately and seek medical advice

Shelf Life & Storage

6 months when stored in a cool dry place, failure to comply with these recommendations will result in a reduction in shelf life

Note

Roll the drum before use to prevent settling out of the product

Note: The information and specifications provided is to the best of our knowledge. The technical data contained herein are true and accurate at the date of issue and are subject to change without prior notice. No guarantee of accuracy is given or implied. We guarantee our products to conform to ASHAKepoxerite Products quality control. We cannot be held responsible or liable, directly or in directly for the use of our products, coverage, performance or injury resulting from use, as we have no control over the method of application used or site conditions. For further technical and method statements, contact our Technical representatives.