



PRODUCT DATA SHEET

PRODUCT CODE: ALL CODES SUPACEM COAT

Description

Supacem coat is a cementitious based decorative waterproof coating which is easily mixed and applied to provide a durable

Principal uses

- Decorative coating on
- Concrete, bricks and plastered walls

Advantages

- Interior and exterior walls
- Tough and durable
- UV resistant

Colours

Supacem coat is available in various colours please consult your local representative

Surface preparation

The substrate must be structurally sound, dry and clean

Limitations

Do not use products in temperatures below 9°C
Avoid excessive heat 30°C and higher

Mixing instructions

Mix ratio volume 3:2. Mix until product is a creamy slurry. Apply product within 40 minutes and keep agitating mixture to ensure a consistent texture.

Application

Apply product with block brush onto surface
For further instruction please consult method statement or apply as per trail area

Yield

50m² per 25kg one coat only, dependent on surface profile

Set time

Allow 3-4 hours between coats.

Packaging

Supacem Coat is available in 25kg bags

Safety & handling

Wear dust masks when mixing. Use gloves, eye protection at all times. Should the product come into contact with eyes, wash immediately and seek medical advice

Shelf Life & Storage

12 months when stored in a cool dry place, failure to comply with these recommendations will result in a reduction in shelf life

Note: The information and specifications provided is to the best of our knowledge. The technical data contained herein are true and accurate at the date of issue and are subject to change without prior notice. No guarantee of accuracy is given or implied. We guarantee our products to conform to ASHAKepoxerite Products quality control. We cannot be held responsible or liable, directly or indirectly for the use of our products, coverage, performance or injury resulting from use, as we have no control over the method of application used or site conditions. For further technical and method statements, contact our Technical representatives.