



## PRODUCT DATA SHEET

**PRODUCT CODE: E160**  
**EPOXY PRIMER**

### **Description**

E160 is a pure epoxy resin used as a primer for epoxy products. The product bonds to steel and concrete and is simple to mix and apply.

### **Principal uses**

- Used as a primer on cured concrete and steel to improve adhesion of epoxy pastes and grouts.
- Used as a primer for Epoxy flooring systems

### **Advantages**

- Good chemical resistance
- Insensitive to moisture
- Excellent substrate penetration

### **Surface preparation**

Remove all loose material, rust and any oil based residue where the product will be applied. This can be done by wire brushing, sanding, grinding or sand blasting the surface

### **Application**

*Mixing-* using a small trowel, mix component A with component B until uniform colour is achieved

*Application-* the product is now applied to the surface by brush. Clean equipment and brushes with *Brush Master C830*

### **Yield**

Coverage will be approximately 4m<sup>2</sup> per litre, this is dependent on the porosity of the substrate.

### **Pot life & Curing**

The product has a 35 minute pot life at an ambient temperature of 25°C. Should the temperature increase, expect an accelerated reaction. In typical applications the product will be touch dry in 60 – 90 minutes and fully cured in 7 days.

### **Limitations**

Working temperature between 5-30°C  
Do not hand mix.

### **Safety & Handling**

Epoxy resin components may cause skin irritation. The product is low in acute oral toxicity. At room temperature, there is exposure to vapours from the product that may cause allergic skin reaction in humans. Safe handling can best be accomplished by adhering to the following rules:

- Work in well ventilated areas
- Wear PVC gloves, safety glasses and aprons
- Remove any residue with soap and water
- In the event of contact with eyes flush with copious amounts of water. Seek immediate medical attention
- Prior to mixing and curing the product is harm full to the environment

### **Packaging**

The product is a 2 component kit.

The following kit sizes are available; 1ℓ, 2ℓ and 5ℓ

### **Shelf Life & Storage**

12 months when stored in a cool dry place, failure to comply with these recommendations will result in a reduction in shelf life

### **Note**

For further instruction please consult your local representative for a method statement on the product

**Note:** The information and specifications provided is to the best of our knowledge. The technical data contained herein are true and accurate at the date of issue and are subject to change without prior notice. No guarantee of accuracy is given or implied. We guarantee our products to conform to ASHAKepoxerite quality control. We cannot be held responsible or liable, directly or in directly for the use of our products, coverage, performance or injury resulting from use, as we have no control over the method of application used or site conditions. For further technical and method statements, contact our Technical representatives.