



PRODUCT DATA SHEET

PRODUCT CODE: P700

PLASTER KEY

Description

Plasterkey is a universal water based bonding aid

straight onto the wet Plasterkey finishing off in a single operation.

Principal uses

Plasterkey has been designed specifically for use in the building industry to bond sand/cement plaster and gypsum plaster to smooth surfaces.

Plasterkey can be added to a sand/cement plaster mix (10 % of water content) to obtain a stronger bond. Plasterkey can be applied by brush or roller.

Advantages

- Improves non-structural bond of cement & gypsum plasters
- No more hacking and chipping of smooth surfaces
- Bonds to sound PVA surfaces
- Easy to use

Coverage

Coverage is \pm 10 square metres per litre

Packaging

Plasterkey is available in 210l, 25l, 10l and 5l buckets

Surface preparation

Surfaces should be free of loose particles, scaling or flaking material. Wire brush & rinse the surface if necessary

Safety & handling

Use gloves and eye protection at all times. Should the product come into contact with eyes, wash immediately and seek medical advice

Application

Soffits and vertical surfaces - coat the prepared surfaces with a scratch coat consisting of 2 parts river sand, 1 part cement and Plasterkey after dust etc. has been removed. The scratch coat can be applied either by throwing it onto the surface with a trowel or block brush. Alternatively use a tyraline machine. Allow the scratch coat to dry and then plaster in the usual manner.

Shelf Life & Storage

12 months when stored in a cool dry place, failure to comply with these recommendations will result in a reduction in shelf life

Where gypsum based plaster is used, apply the Plasterkey to the prepared surface and plaster

Note: The information and specifications provided is to the best of our knowledge. The technical data contained herein are true and accurate at the date of issue and are subject to change without prior notice. No guarantee of accuracy is given or implied. We guarantee our products to conform to ASHAKepoxerite quality control. We cannot be held responsible or liable, directly or indirectly for the use of our products, coverage, performance or injury resulting from use, as we have no control over the method of application used or site conditions. For further technical and method statements, contact our Technical representatives.