



PRODUCT DATA SHEET

PRODUCT CODE: P710

TILEPRIME

Description

TilePrime is a waterbased copolymer latex

Principal uses

- TilePrime is manufactured specifically as a primer for ceramic wall tiles and melamine surfaces.

Advantages

- Transform old wall tiles with paint
- Transform old melamine cupboards with paint
- Economical and easy to use
- Excellent adhesion to glossy surfaces
- Compatible with most paints

Surface preparation

Clean and dry surface to be primed. Ensure that all dirt, grease and mould is removed. Fill chips or defects with the appropriate filler before priming

Application

Stir before use. Apply an even coat by brush or roller. Touch dry in 1 hour overcoat in 24hours. Clean tools with water after use. Overcoat with any colour quality wall paint of your choice

Coverage

Spreading rate $\pm 10\text{m}^2$ per litre

Packaging

Tileprime is available in 210l, 25l and 5l buckets

Safety & handling

Use gloves and eye protection at all times. Should the product come into contact with eyes, wash immediately and seek medical advice

Shelf Life & Storage

12 months when stored in a cool dry place, failure to comply with these recommendations will result in a reduction in shelf life

Note

THE PAINTING OF KITCHEN WORKTOPS IS NOT RECOMMENDED

Note: The information and specifications provided is to the best of our knowledge. The technical data contained herein are true and accurate at the date of issue and are subject to change without prior notice. No guarantee of accuracy is given or implied. We guarantee our products to conform to ASHAKepoxerite quality control. We cannot be held responsible or liable, directly or in directly for the use of our products, coverage, performance or injury resulting from use, as we have no control over the method of application used or site conditions. For further technical and method statements, contact our Technical representatives.