



PRODUCT DATA SHEET

STRIPSOLVE

Description

Stripsolve is a hydrocarbon releasing agent, for the construction industry

Principal uses

- A simple one coat application
- An economical release agent for timber and steel shuttering
- Stripsolve does not evaporate in the sun
- Build up on shutter is eliminated
- Cleaning is minimised

Performance data

Appearance:	Dark Coloured Oil
Temperature Stability:	40°C
Flash Point:	198°C
Odour:	Slight
Viscosity:	approx 46
Physical Form:	Liquid

Application

By paint roller, brush or low pressure spray. Apply as thinly as possible to the entire surface of the shutter. Coverage is approximately 10 square metres per litre

Packaging

Stripsolve is available in 1000l, 250l and 25l drums

Safety & handling

Use gloves and eye protection at all times. Should the product come into contact with eyes, wash immediately and seek medical advice

Shelf Life & Storage

12 months when stored in a cool dry place, failure to comply with these recommendations will result in a reduction in shelf life

Note

WARNING:

As Stripsolve has a dark colour some staining of the concrete may occur

Where concrete finish is critical use Superstrip. As Stripsolve is a laundered oil, the colour and viscosity may vary

Always roll the drum before using to ensure no settlement of the ingredients has taken place

Note: The information and specifications provided is to the best of our knowledge. The technical data contained herein are true and accurate at the date of issue and are subject to change without prior notice. No guarantee of accuracy is given or implied. We guarantee our products to conform to ASHAKepoxerite Products quality control. We cannot be held responsible or liable, directly or in directly for the use of our products, coverage, performance or injury resulting from use, as we have no control over the method of application used or site conditions. For further technical and method statements, contact our Technical representatives.