



## PRODUCT DATA SHEET

### **SUPERSTRIP**

#### **Description**

Superstrip is a Mineral oil based releasing agent for the construction and pre-cast industry

#### **Principal uses**

- A simple one coat application.
- An economical release agent for timber, steel and fibreglass shuttering.
- Superstrip does not evaporate in the sun.
- Build up on the shutter or mould is eliminated.
- Coverage is approximately 14-20 square metres per litre.
- Cleaning is minimised

#### **Performance data**

Appearance: Light/Medium coloured Oil  
Temperature Stability: 40°C  
Flash Point: 198°C  
Odour: Slight  
Viscosity: 46  
Physical Form: Liquid

#### **Application**

Apply as thinly as possible to entire surface of shutter or mould by means of a paint brush, paint roller or low pressure spray.

#### **Packaging**

Superstrip is available in 1000ℓ, 210ℓ and 25ℓ drums

#### **Safety & handling**

Use gloves and eye protection at all times. Should the product come into contact with eyes, wash immediately and seek medical advice

#### **Shelf Life & Storage**

12 months when stored in a cool dry place, failure to comply with these recommendations will result in a reduction in shelf life

#### **Note**

Roll the drum before use to prevent settling out of the product.

**Note:** The information and specifications provided is to the best of our knowledge. The technical data contained herein are true and accurate at the date of issue and are subject to change without prior notice. No guarantee of accuracy is given or implied. We guarantee our products to conform to ASHAKepoxerite Products quality control. We cannot be held responsible or liable, directly or indirectly for the use of our products, coverage, performance or injury resulting from use, as we have no control over the method of application used or site conditions. For further technical and method statements, contact our Technical representatives.